

PB03 Broadband Printer



- The PBO3 broadband printer is designed to integrate with the CPO3 pinpad and offers huge savings to corporate customers over traditional dial-up options by connecting via TCP/IP and routing through their existing Virtual Private Network (VPN) where available. If a client does not have a VPN Cadmus can assist by providing access via the Cadmus VPN 'secure tunnel' linking direct to Cadmus servers.

Other printers available: see Cadmus Printers Spec Sheet

- PRO3
- PMO3
- PVO4

AT A GLANCE

Standard 57mm thermal printer with built-in 10 BaseT ethernet interface

Ideal corporate solution and a cost effective alternative to dial-up landline

TCP/IP

TECHNICAL SPECIFICATIONS

16 Bit Processor

512K NV RAM

1MB Flash Ram Standard - optional up to 4MB

Ports:

PBO3: RJ12 RS232 for PIN pad
RJ45 RS232
RJ45 10 BaseT port

Dimensions: (LxWxHmm) 180 x 115 x 95

Weight: 400gms

15 lines per inch, 57 x 57mm Thermal printer

TCP/IP

Cadmus Technology Limited (and/or its subsidiaries, associates or parent companies) ("Cadmus") reserves the right to make changes to this document at any time and without notice. The information furnished by Cadmus in this publication is believed to be accurate and reliable; however, no responsibility is assumed by Cadmus for its use, nor for infringements of patents or other rights of third parties resulting from its use. No license is granted under any patents or patent rights owned by Cadmus.

